ADWF480-xx Series

DESCRIPTIONS 480W, AC/DC DIN-Rail Power Supply

RoHS 3 Years Warranty

CE Report UKCA Report

EN62368-1 BS EN62368-1

FEATURES

- Universal 180-600VAC or 250-850VDC Input voltage
- Active PFC, PF up to 0.95
- Operating ambient temperature range: -40℃ to +85℃ (50℃ full load)
- Supports single and dual phase input
- High efficiency, high reliability
- LED indicator for output status
- 150% peak power lasts for 3s
- Output short circuit, over-current,over-voltage, over-temperature protection
- DC OK function
- Double-sided conformal coating
- Operating altitude up to 5000m
- OVC III, 2000m altitude (design refer to EN61010)
- Design refer to UL508, UL61010, UL/IEC62368

APPLICATIONS

- Industrial Control Equipment
- Factory automation
- mechanical equipment

Selection Guide

Certification	Part No.	Output Power	Nominal Output Voltage and Current	Output Voltage Adjustable Range	Efficiency at 400VAC (%) Typ.	Max. Capacitive Load (μF)
EN/BS EN	ADWF480-24	480	24V/20A	24-28	93	20000
	ADWF480-48		48V/10A	48-55	94	10000

Note:1. *The actual adjustment range may extend outside the values stated, care should be exercised to ensure that the output voltage and power levels remain within the published maximum values.

2.*The product picture is for reference only, for details, please refer to the actual product.

Specifications

Product Specifications	Item	Operating Conditions		Min.	Typ.	Max.	Unit
Input Specifications	Input Voltage Range	Rated input (certified voltage)		200	--	480	VAC
		AC input		180	--	600	
		DC input		250	--	850	VDC
	Input Voltage Frequency			47	--	63	Hz
	Input Current	230VAC		--	--	4	A
		400VAC		--	--	1.6	
	Inrush Current	400VAC	Cold start	--	30	--	
	Power Factor	230VAC	Normal temperature, rated load	0.93	0.95	--	--
		400VAC		0.92	0.94	--	
	Start-up Delay Time			--	0.8	--	s
	Leakage Current	480VAC		< 0.5mA **RMS**			
	Hot Plug			Unavailable			
Output Specifications	Output Voltage Accuracy	Full load range		--	±1	--	%
	Line Regulation	Rated load		--	±0.5	--	
	Load Regulation	0% - 100% load		--	±1	--	
	Ripple & Noise*	20MHz bandwidth (peak-to-peak value)	24V	--	--	100	mV
			48V	--	--	150	
	Temperature Coefficient	0℃ to +50℃		--	±0.03	--	%/℃
	Minimum Load			0	--	--	%
	Dynamic Minimum Load			10	--	--	
	Stand-by Power Consumption	400VAC		--	4	--	W
	Hold-up Time	400VAC/500VAC		--	20	--	ms
	150% peak load power	400VAC		Continuous work 3s			
	Short Circuit Protection			Enter hiccup mode after constant current operation for 3s (typ.), continuous, self-recovery			
	Over-current Protection			≥130% Io, enter hiccup mode after constant current operation for 3s (typ.), self-recovery			
	Over-voltage Protection	24V		≤33VDC	Hiccup, self-recovery		
		48V		≤63VDC			
	Over-temperature Protection	Rated load	Over-temperature protection start	--	--	80	℃
			Over-temperature protection release	55	--	--	

General Specifications	Isolation	Input - output	Electric strength test for 1min., leakage current < 5mA	4000	--	--	VAC
		Input - ⏚		2000	--	--	
		Output - ⏚		500	--	--	
		Output - DC OK	Electric strength test for 1min., leakage current < 1mA	500	--	--	
	Insulation Resistance	Input - output	Test voltage: 500VDC	100	--	--	MΩ
		Input - ⏚					
		Output - ⏚					
		Output - DC OK					
	Operating Temperature			-40	--	85	℃
	Storage Temperature			-40	--	85	
	Operating Humidity		Non-condensing	--	--	95	%RH
	Storage Humidity			--	--	95	
	Output Power Derating	Operating temperature derating	-40℃ to -30℃	5.0	--	--	%/℃
			+50℃ to +70℃	2.0	--	--	
			+70℃ to +85℃	3.33	--	--	
		Input voltage derating	180 - 200VAC	0.5	--	--	%/VAC
			550 - 600VAC	0.4	--	--	
		Altitude derating	2000m - 5000m	3.5	--	--	%/Km
	Safety Class			CLASS I, ANSI/ISA71.04-2013			
	MTBF		MIL-HDBK-217F@25℃	≥300,000 h			
Environmental Characteristics	Sinusoidal Vibration		10 - 500Hz, 2g, three directions of X, Y, Z axis	GB2423.10、IEC60068-2-6			
	High and Low Temperature Working		+85℃, -40℃	GB2423.1、IEC60068-2-1			
	Low Temperature Storage		-40℃	GB2423.1、IEC60068-2-1			
	High Temperature Storage		+85℃	GB2423.2、IEC60068-2-2			
	High Temperature Aging		+50℃	GB2423.2、IEC60068-2-2			
	Normal Temperature Aging		+25℃	GB2423.1、IEC60068-2-1			
	Temperature Shock		-40℃ to +85℃	GB2423.22、IEC60068-2-14			
	Temperature Cycle		-30℃ to +50℃	GB2423.22、IEC60068-2-14			
	Hot and Humid		+85℃, 85%RH, 12h	GB2423.50、IEC60068-2-67			
Mechanical Specifications	Case Material		Metal (AL5052, SPCC)				
	Dimensions		80.00 x 124.00 x 127.00mm				
	Weight		1145g (Typ.)				
	Cooling Method		Free air convection				

Note: 1.*The "Tip and barrel method" is used for ripple and noise test, output parallel 47uF electrolytic capacitor and 0.1uF ceramic capacitor.
2.*Full input voltage at room temperature, <5%Io range, 300mv (Max.).

Electromagnetic Compatibility (EMC)

Electromagnetic Compatibility (EMC)	Emissions	CE	CISPR32/EN55032 CLASS B	
		RE	CISPR32/EN55032 CLASS B	
		Harmonic current	IEC/EN61000-3-2 CLASS A	
		Voltage flicker	IEC/EN61000-3-3 Fulfilled	
	Immunity	ESD	IEC/EN61000-4-2 Contact ±8KV/Air ±15KV	Perf. Criteria A
		RS	IEC/EN61000-4-3 10V/m	Perf. Criteria A
		EFT (input port)	IEC/EN61000-4-4 ±4KV	Perf. Criteria A
		EFT (output port)	IEC/EN61000-4-4 ±2KV	Perf. Criteria A
		EFT (DC OK port)	IEC/EN61000-4-4 ±1KV	Perf. Criteria A
		Surge (input port)	IEC/EN61000-4-5 Line to line ±2KV/line to PE ±4KV	Perf. Criteria A
		Surge (output port)	IEC/EN61000-4-5 Vo+ to Vo- ±500V/Vo+/Vo- to PE ±1KV	Perf. Criteria A
		Surge (DC OK port)	IEC/EN61000-4-5 DC OK to PE, ±1KV	Perf. Criteria A
		CS	IEC/EN61000-4-6 10Vr.m.s	Perf. Criteria A
		PFMF	IEC/EN61000-4-8 30A/m	Perf. Criteria A
		Voltage dips, short interruption and voltage variations	IEC/EN61000-4-11 100% dip 1 periods, 30% dip 25 periods (50Hz), 30 periods (60Hz)	Perf. Criteria B

Product Characteristic Curve







Over-current protection curve (Typ.)



Short circuit protection curve (Typ.)



Note: 1. With an AC input voltage between 180 - 200VAC/550-600VAC/250 - 280VDC/780-850VDC the output power must be derated as per the temperature derating curves;

2. This product is suitable for applications using natural air cooling.





Installation Diagram





Materials required in the installation		
1	Product	1 PCS
2	Phillips screwdriver Slotted screwdriver	1 PCS
3	TS35/7.5 or TS35/15	1 PCS
4	24–10AWG Wire	/ PCS
	The content is for reference only. Regarding the actual wire diameter and tightening torque, refer to the dimensional drawing.	

Product

Phillips screwdriver
Slotted screwdriver
Diameter of the cutting
Diameter: 3mm



TS35/7.5 or TS35/15



24–10AWG Wire

Installation Steps ①–②



Disassembly Steps ③–④



Note: Keep the following installation clearances: 20mm on top, 20mm on the bottom, 5mm on the left and right sides are recommended when the device is loaded permanently with more than 50% of the rated power. Increase this clearance to 15mm in case the adjacent device is a heat source (e.g. another power supply).

Dimensions and Recommended Layout



THIRD ANGLE PROJECTION

Pin-Out	
Pin	Mark
1	DC OK
2	
3	-Vo
4	-Vo
5	+Vo
6	+Vo
7	L1
8	L2
9	⏚

9、10 any position must be connected to the earth(⏚)

Note:
Unit: mm[inch]
DC ON：Output status indicator LED
ADJ: Output adjustable resistor
Wire range: Input: 20-10 AWG
(12-10AWG for pin9)
Output: 24V: 14-10AWG
48V: 18-10AWG
DC OK: 24-16AWG
Input Tightening torque: Max 0.5 N・m
Output Tightening torque: Max 0.5 N・m
Mounting rail: TS35, rail needs to connect safety ground
General tolerances: ± 1.00[± 0.039]

WARNING Risk of electrical shock, fire, personal injury or death:

AVERTISSEMENT AVERTISSEMENT Risque de choc électrique, d'incendie, de blessures corporelles ou de décès :

1. Do not use the power supply without proper grounding (Protective Earth). Use the terminal on the input block for earth connection and not one of the screws on the housing;
   N'utilisez pas l'alimentation électrique sans mise à la terre appropriée (Terre protectrice). Utilisez le terminal sur le bloc d'entrée pour la connexion terrestre et non pas une des vis sur le boîtier;
2. Turn power off before working on the device, protect against inadvertent re-powering;
   Éteignez l'alimentation avant de travailler sur l'appareil, protégez-vous contre la réénergisation accidentelle;
3. Make sure that the wiring is correct by following all local and national codes;
   Assurez-vous que le câblage est correct en suivant tous les codes locaux et nationaux;
4. Do not modify or repair the unit; Do not open the unit as high voltages are present inside;
   Ne modifiez pas ou ne réparez pas l'appareil; Ne modifiez pas ou ne réparez pas l'appareil;
5. Use caution to prevent any foreign objects from entering the housing;
   Faire preuve de prudence pour empêcher les objets étrangers d'entrer dans le logement;
6. Do not use in wet locations or in areas where moisture or condensation can be expected;
   Faire preuve de prudence pour empêcher les objets étrangers d'entrer dans le logement;
7. Do not touch during power-on, and immediately after power-off, hot surfaces may cause burns;
   Ne touchez pas pendant l'alimentation et, immédiatement après l'alimentation, les surfaces chaudes peuvent causer des brûlures.
8. For ambient temperature ≤60℃, use ≥90℃ - copper wire only; for ambient temperature >60℃ to 85℃, use ≥105℃ - copper wire only;
   Température ambiante ≤60℃, utiliser ≥90℃ - seulement fils de cuivre; Température ambiante >60℃ et 85℃, utiliser ≥105℃ - seulement fils de cuivre;
9. use only wires with a minimum dielectric strength of 300V (input) and 60V (output);
   Uniquement pour l'ulilisation de fils de cuivre d'une résisitance d'isolation minimale de 300V (d'entrée) et 60V (de sortie).

Note:

1. Unless otherwise specified, parameters in this datasheet were measured under the conditions of Ta=25℃, humidity<75% RH with nominal input voltage and rated output load;
2. The room temperature derating of 3.5℃/1000m is needed for operating altitude greater than 2000m;
3. All index testing methods in this datasheet are based on our company corporate standards;
4. In order to improve the efficiency at high input voltage, there will be audible noise generated, but it does not affect product performance and reliability;
5. We can provide product customization service, please contact our technicians directly for specific information;
6. Products are related to laws and regulations: see "Features" and "EMC";
7. The out case needs to be connected to the earth (⏚)of system when the terminal equipment in operating;
8. The output voltage can be adjusted by the ADJ, clockwise to decrease;
9. Our products shall be classified according to ISO14001 and related environmental laws and regulations, and shall be handled by qualified units;
10. The power supply is considered a component which will be installed into a terminal equipment. All EMC tests should be confirmed with the final equipment. Please consult our FAE for EMC test operation instructions.